

The Latest Technology to Beat Your Competitors

CaraPro Single-Coat-Clear/Stain Wood Sealers

SUBSTANTIALLY LOWER LABOR COSTS

- Single Coat Coverage
- Easy Spray / Roll Application
- Higher moisture content wood – problem solved!
- Approx. Coverage – Spray: 300 sq. ft. per gal.
- Quick Drying in only 15 minutes
- No Laps, Runs, or Streaks
- Non-slip, Won't Wash Away

Available in a Clear/Natural Finish or Variety of Colors

Natural Oak	Irish Oak
Sugar Maple	California Redwood
Texas Pecan	Western Red Cedar
Genuine Mahogany	American Chestnut
Dark Walnut	Black Walnut



CaraPro delivers what you want:

A Better Product – CaraPro uses advanced technology to deliver superior protection that helps your company stand out from the competition. Bringing unique looks and appeal to every project can now be your trademark.

Better Margins – CaraPro is designed for increased income potential and a beautiful finish to help grow your business. The growing demand for CaraPro products from property managers, architects, designers, operations managers, manufacturing facilities and homeowners will go directly to you, the contractor.

You Will Love CaraPro

Keep wood looking new for longer.
Don't replace it, transform it!



Retain and accentuate the natural grain and finish

WE RECOMMEND REAPPLICATION EVERY:

- 3-7 years to maintain the level of protection
- 3 years to protect the natural beauty

Coverage will vary depending on the type of wood, its porosity, texture and condition. The color (pigments) of all stains change over time.

Longevity of protection depends upon weathering conditions, original state of wood and correct application following best practices.

Horizontal surfaces, and those allowing water to pool may require more frequent reapplication.

For application to hardwoods, please contact us for information on current best practices and results.

INTEGRICOTE

5000 Gulf Freeway, Bldg 7, Suite 100
Houston, TX 77023

To learn more please call (888) 790-2468 or visit
www.integricote.com

Copyright 2016 Integricote Inc. This document is subject to change without prior notice and the information provided is a general description of CaraPro Single-Coat-Clear/Stain Wood Sealers. Please contact us for specific information for your application. Printed in the USA

Make Wood Look Better & Last Longer

New Wood Sealers from

INTEGRICOTE

A Leader in Developing Nanotechnology

Products made in the USA for
the Construction Industry

CaraPro™

SEAL FROM WITHIN



Single-Coat
Clear/Stain Wood Sealers

Finally! Cost Effective Technology Delivering Long-Term Protection

Lower Cost – One coat coverage means lower cost per square foot than all leading competitors, less labor cost and quicker project completions!

Advanced Technology – Means the applied stains are locked into the wood and will not wash out.

What is CaraPro?

CaraPro is State-of-The-Art! It Changes the Way You Seal, Stain and Protect Wood.

For you: CaraPro offers lower total project costs through easier application - only one coat - greater coverage areas - ~300 sq. ft./gal. - and far lower labor costs.

CaraPro Sealers offer greater profit margins, repeat customers, and increased demand by delivering unique finishes and long-term protection.

CaraPro Sealers are unique as they are formulated to:

- Extend the life expectancy of all exterior wood products.
- Enhance natural beauty while protecting the integrity of the wood from the effects of water exposure and erosion.
- Dry in less than 15 minutes, withstand foot traffic after one hour and rain after just three hours.

For your customers: CaraPro technology delivers unrivalled, superior performance and protection.

Oil-Resin & Acrylic/Urethane products may only work with wood that is almost completely dry, with a moisture content measured at **12% or below**.

This can mean your customers have to wait weeks, or months before application can even begin.

AND

Oil-resin sealers lock in moisture causing wood to slowly rot from within.

CaraPro Single-Coat Clear/Stain Sealers:

- Worry-free: apply easily to higher moisture content wood.
- Creates a unique, breathable, 2-way barrier that allows water vapor to escape but stops liquid water from entering.
- Specifically engineered to deeply penetrate and form a highly durable, interlocking network throughout the wood.
- Will not dissolve in water or wash out due to exposure, Oils never fully dry, they leach out and wash away over time.

Instructions

For Best Results including Appearance, Longevity of Protection and Ease of Application, please take note of the following steps and tips:

Surface Preparation - The surface should be clean and ideally have a moisture content below 20%. A clean surface is free of dust, dirt, oil, and grease.

If application is to be done on aged-wood, already exposed to weathering for a long period of time; removal of algae, mold, and mildew will improve the look and performance.

ALL OTHER SEALERS AND STAINS MUST BE FULLY STRIPPED / REMOVED BEFORE APPLICATION.

Caustic or acidic strippers and cleaners must be carefully neutralized prior to application.

Before Application – Ensure the surface is adequately prepared. Test a small, inconspicuous area to ensure the desired finish is achieved.



CAUTION

KEEP OUT OF REACH OF CHILDREN – DO NOT TAKE INTERNALLY
MANTENER FUERA DEL ALCANCE DE LOS NIÑOS - NO INGERIR

Avoid Overspray And Do Not Allow Product To Come Into Contact With Porous Surfaces - Like Concrete... Cover All Surrounding Areas During Application. Protect Plants/ Greenery As They May Become Discolored By The Pigments.

Any Porous Surface Coming Into Contact With Product Will Be Permanently Stained.

If any area is unintentionally exposed to the stain, immediately wipe off and carefully flush porous surfaces with denatured alcohol.

Application Tips

SHAKE WELL BEFORE USE & AT LEAST EVERY 30 MINUTES DURING USE

Combine multiple containers together to ensure a consistent stain color.

DO NOT THIN, MIX OR ADD TO OTHER PRODUCTS

Be certain that you have at least a 3 hour window before rain, or any other source of water comes into contact with the finished surface. As a general rule, never allow water sprinklers to be aimed or directed at wood.

APPLY ONE EVEN COAT ALONG THE WOOD GRAIN

SMALLER AREAS

Intricate work and smooth to semi-smooth surfaces: Use a foam brush, high density, closed cell foam roller cover or stain pad.

Rougher surfaces: Use a high density, knit polyester roller cover

LARGER AREAS

A suitable, methanol compatible, Air-Sprayer or Airless-Sprayer may be used. The recommended tip orifice size varies depending on your exact setup and pressure used. In general a 0.013 – 0.019 inch tip orifice size will work for most applications.

If too much stain is applied to a certain area, it may be back-brushed or use a stain-pad to get a consistent finish. To ensure that there is minimal variation in stain color, this should be done within 5 minutes of the first application.

STORAGE, CLEAN-UP & DISPOSAL

Moisture sensitive; keep container tightly closed when not in use. Do not allow to freeze. Store in a cool, well-ventilated area, out of direct-sunlight.

Clean / flush / wipe down all equipment and tools with denatured alcohol.

For disposal of empty containers and unused product, please contact your local refuse collection service.